



Office of the Monroe County Surveyor
Trohn Enright-Randolph

Health Services Building
119 West 7th Street
Bloomington, IN 47404
Phone: (812) 349-2570

Dear User,

The following images were obtained in 2017 by the Office of the Monroe County Surveyor from the State Imaging and Microfilm Laboratory at the Indiana State Archives. The field notes and plats for Lawrence County are stored on microfilm Reel 1903 at the Indiana State Archives. Each page provided by the State Imaging and Microfilm Laboratory is approximately 18MB. Our office combined the pages by Township & Range and reduced the resulting pdfs. This process may have caused some degradation in quality. We will provide unreduced images of specific pages if required. Please contact us at 812-349-2570 or at SurveyorsOffice@co.monroe.in.us to request a higher quality image of any specific page.

The pdfs are bookmarked with the original page numbers as assigned by the State Imaging and Microfilm Laboratory.

Be prepared to provide the county name, reel number, and the required page numbers when requesting full sized images.

If you would like a DVD of an entire county, please provide us with one DVD per county along with a self-addressed, stamped envelope.

Trohn Enright-Randolph
Monroe County Surveyor

Township No. 6. North of Range No. 2 West 2nd Mer. Indian

South Boundary

G. 46.

East Quakamam line On the South Boundary of sec. 31
T. 6. N. R. 2 W.
40.55 To a Rock 100 links wide, corner S.
40.00 Set a timber post in the post.
62.49 To the above named Rock 100 links wide, corner N.
80.00 Set a timber post for the cor. of sec. 31 & 32.
Lands rich and rolling. Timber Oak, Poplar, & Walnut,
and 8th Spruce.

East Quakamam line On the South Boundary of sec. 32
T. 6. N. R. 2 W.
35.23 To a Rock 100 links wide, corner S.
40.00 Set a timber post in the post.
80.00 Set a timber post for the cor. of sec. 32 & 33.
Lands the same as last mile.

East On the Quakamam line On the South Boundary of
sec. 33 T. 6. N. R. 2 W.
40.00 Set a timber post in the post.
80.00 Set a timber post for the cor. of sec. 33 & 34.
Lands very bushy & hilly. Thin soil.

East On a Quakamam line On the South Boundary of sec. 34
T. 6. N. R. 2 W.
40.00 Set a timber post in the post.
80.00 Set a timber post for the cor. of sec. 34 & 35.
Lands the same.

East On a Quakamam line On the South Boundary of sec. 35
T. 6. N. R. 2 W.
40.00 Set a timber post in the post.
80.00 Set a timber post for the cor. of sec. 35 & 36.
Lands very hilly bushy.

T. A. C. A. R. A. N. 272nd Mm. Ind.

East	On a Random line On the South Boundary of sec. 36. T. 6. N. R. 27.
4000	Set a temporary post.
77.75	Enter out the N. 5 th in Range line 12 th & 9 th Mm. North of the post on of S. 5 th 6. N. R. 27. 11 th W. Lands not so bushy Timber Oak & Hickory
West	On the line between Sec. 1. 36. T. 6. N. R. 27. G. 48
4000	Set the temporary post on the line from which, North 10 in dia. bears S 70 E. 27 th 10 th dist. 20, No. 10 a a a S 84 N. 8. "
8000	Set the temporary post on the line from the cor. of sec. 35. 36. from which, Run 10 in dia. bears N 89 E. 10 th 10 th dist. and a Dogwood 6 a a a N 51 E. 29. "
West	On the line On the South Boundary of sec. 35. T. 6. N. R. 27.
4000	Set the temporary post at the line from which, North 10 in dia. bears West 2 nd timber creek, 20
8000	Set the temporary post on the line from the cor. of sec. 34. 35. from which, Run 10 in dia. bears N 67 W. 6 th 10 th dist. and a Sugar. 8 a a a N 55 E. 22. "
West	On the line On the South Boundary of sec. 34. T. 6. N. R. 27.
4000	Set a temporary post on the line from which, Poplar, 20 in dia. bears N 36 E. 18 th 10 th dist. 20,
8000	Set the temporary post on the line from which, 3. 35. 36. Run. 9 in dia. bears S 80 E. 37 th 10 th dist. 20, No. 20 a a a N 37 E. 15. "
West	On the line On the South Boundary of sec. 33. T. 6. N. R. 27.

T. A. C. A. R. A. N. 272nd Mm. Ind.

4000	Set the temporary post at the line from which, in a bush thicket No timber high.
8000	An Sumner 5 in dia. stands from the cor. of sec. 32. 33.
West	On the line On the South Boundary of sec. 32. T. 6. N. R. 27.
4000	Set a temporary post on the line from which, Run 10 in dia. bears S 85 E. 16 th 10 th dist. 20, No. 10 a a a N 26 W. 15. "
8000	Set a post temporary on the line from the cor. of sec. 31. 32. from which, Run 10 in dia. bears N 44 E. 9 th 10 th dist. and a No. 8 a a a N 13 W. 14. "
West	On the line On the South Boundary of sec. 31. T. 6. N. R. 27.
14.26	To the Rock This line is continued no farther West.
East Boundary.	
North	On the East Boundary of sec. 36. T. 6. N. R. 27.
4000	Set a temporary post from which, North 10 in dia. bears S 99 E. 26 th 10 th dist. 20, No. 12 a a a N 49 W. 32. "
8000	Set a post for the cor. of sec. 35. 36. from which, Dogwood 6 in dia. bears S 99 E. 34 th 10 th dist. 20, Gum. 9 a a a S 80 E. 31. "
	Lands rolling Timber Oak & Hickory. Poplar & Rock
North	On the East Boundary of sec. 35. T. 6. N. R. 27.
13.50	To a 7 th Oak 12 in dia. in the line.
4000	Set a temporary post from which, Run 10 in dia. bears N 15 W. 40 th 10 th dist. 20, No. 22 a a a Sec. 19. "
8000	Set a post for the cor. of sec. 34. 35. from which,

T. N. C. A. R. N. 2nd 2nd Mr. Ind.

Beck. 18 in dia^r beam N 78 E. 22 1/2 m. dist. 8 a.
 Do. 10 " " " N 47 W. 23 " "
 Sands the same.

North On the East Boundary of sec. 24. T. 6. N. R. 2 W.
 1300 To a N Oak, 20 in dia^r in the mi.
 4000 Set a p. su. post from which,
 Hick 10 in dia^r beam S 25 E. 28 1/2 m. dist. 10 a.
 Daywood 6 " " " N 11 W. 23 " "
 76.00 To a Brook 10 links m. d., Come E.
 80.00 Set a post for the cor of sec. 13 & 24 from which,
 Poplar 12 in dia^r beam S 30 W. 30 1/2 m. dist. 10 a.
 Beck 20 " " " N 35 E. 15 " "
 This post stands in a spring Come E.
 Set on this mile line. Timber Oak, & Beck,
 My Drive &c.

North On the East Boundary of sec. 13 T. 6. N. R. 2 W.
 4000 Set a p. su. post from which,
 N Oak 7 in dia^r beam N 17 W. 23 1/2 m. dist. 10 a.
 N Oak 20 " " " N 60 E. 20 " "
 76.75 To a Brook 10 links m. d., Come E.
 80.00 Set a post for the cor of sec. 12 & 13 from which,
 Beck 20 in dia^r beam N 65 E. 4 1/2 m. dist. 10 a.
 Do. 20 " " " S 36 W. 26 " "
 Sands the same.

North On the East Boundary of sec. 12. T. 6. N. R. 2 W.
 4000 Set a p. su. post from which,
 Sugar 6 in dia^r beam S 25 E. 7 1/2 m. dist. 10 a.
 Do. 8 " " " N 80 W. 14 " "
 80.00 Set a post for the cor of sec. 1 & 12 from which,
 Hick 10 in dia^r beam S 71 E. 5 1/2 m. dist. 8 a.

T. N. C. A. R. N. 2nd 2nd Mr. Ind.

Sugar. 12 in dia^r beam N 8 E. 25 1/2 m. dist.
 Sands with Timber Sugar, Beck, &c.

North On the East Boundary of sec. 1. T. 6. N. R. 2 W.
 1550 To a Poplar, 24 in dia^r in the mi.
 4000 Set a p. su. post from which,
 N Oak 10 in dia^r beam S 26 W. 7 1/2 m. dist. 8 a.
 Immersed 5 " " " N 10 E. 16 " "
 49.00 To a Poplar, 30 in dia^r in the mi.
 80.00 Set a post at the distance of five miles from the South
 Boundary for the cor of T. 6 N. R. 2 W.
 Sands the same.
 Surveyed by A. H. H. H.
 Sept 19 1811.

North Boundary.
 West On the South Boundary of sec. 36 T. 7. N. R. 2 W.
 24.75 To a Walnut 30 in dia^r in the mi.
 4000 Set a p. su. post; Cor. on a N Oak 36 in dia^r
 65.00 To a Sugar, 18 in dia^r in the mi.
 80.00 Set a post for the cor of sec. 35 & 36 from which,
 Beck 16 in dia^r beam S 35 W. 3 1/2 m. dist. 10 a.
 Do. 16 " " " N 65 E. 44 " "
 Sands with Timber Sugar, Walnut, Ash, Beck, &c.

West On the South Boundary of sec. 35 T. 7. N. R. 2 W.
 4000 Set a p. su. post from which,
 Sugar 8 in dia^r beam N 56 W. 5 1/2 m. dist. 10 a.
 Do. 10 " " " S 86 E. 23 " "
 69.00 To a N Oak, 18 in dia^r in the mi.
 80.00 A N Oak, 24 in dia^r beam for the cor of sec. 34 & 35
 from which Sugar, 12 in dia^r beam N 53 E. 12
 April 2nd 1811.

T. N. C. N. R. N. 27th 2nd M. Ind.

West On the South Boundary of sec. 34. T. 1. N. R. 27th
 35.50 To an Oak, 30 in dia. bet the line.
 40.00 Set a 7th supst from which,
 Buck 30 in dia. bet. S 57 E. 12 links dist. to
 Loc. 20 " " " N 27 W. 14 " "
 65.00 To a Brook 6 links under Corner S. W.
 80.00 Set a post for the cor of sec. 33 & 34 from which,
 N Oak, 18 in dia. bet. S 25 N 31 W dist. to
 Sugar. 14 " " " N 65 E. 20 " "
 Good level Timber Oak,

West On the South Boundary of sec. 33. T. 1. N. R. 27th
 15.00 To a Brook 10 links under Corner S.
 30.00 " " " " " " S. E.
 40.00 Set a 7th supst from which,
 Buck. 14 in dia. bet. S 44 E. 7 links dist. to
 Sugar. 9 " " " " N 81 W. 17 " "
 80.00 Set a post for the cor of sec. 32 & 33 from which,
 Buck 24 in dia. bet. S 6 E. 17 links dist. to
 Sugar. 8 " " " " N 67 W. 10 " "
 Good level and rich Timber Buck, Sugar, Oak

West On the South Boundary of sec. 33. T. 1. N. R. 27th
 25.00 To a spring Corner S.
 37.00 " " " " " " S. W.
 40.00 Set a 7th supst from which,
 N Oak 16 in dia. bet. S 43 E. 14 links dist. to
 Buck 15 " " " " " " S 67 W. 31 " "
 60.00 To a Brook 3 links under Corner S.
 80.00 Set a post for the cor of sec. 31 & 32 from which,
 Gum. 15 in dia. bet. S 87 W. 25 links dist. to
 Buck 6 " " " " " " N 84 E. 31 " "
 Good Oak & Sugar,

T. N. C. N. R. N. 27th 2nd M. Ind.

West On the South Boundary of sec. 34. T. 1. N. R. 27th
 20.00 To a Brook 3 links under Corner S.
 35.00 To a Brook 18 in dia. bet the line.
 40.00 Set a 7th supst from which,
 N Oak 24 in dia. bet. S 67 E. 25 links dist. to
 Walnut 20 " " " " " " N 47 W. 24 " "
 60.00 To a spring Corner N.
 80.00 Set a timber post for the cor of T. 6 N. R. 27th 3rd
 Went in search of the Range line. Travelled 3 miles
 South; hunted but could not find it.

West Boundary
 South to the timber post set on the 2nd Int and
 run a Remann line South Between Ranges 213th
 T. 6 N. 6 miles to 3 chains, fell 18 chains West of
 Harris' Town. Cor.
 North On the East Boundary of sec. 36. T. 6 N. R. 3rd W.
 21.00 To a Brook. 200 links under Corner S. E. kept up the
 creek near the middle
 37.00 Left the creek to the West
 40.00 Set a 7th supst from which,
 Buck. 14 in dia. bet. S 67 N. 10 links dist. to
 Buckeye 8 " " " " " " N 44 E. 5 " "
 60.00 To a N Oak 24 in dia. bet the line.
 80.00 Set a post for the cor of sec. 35 & 36 from which,
 Buck. 16 in dia. bet. S 57 W. 14 links dist. to
 Loc. 14 " " " " " " S 1 E. 20 " "
 April 6. 1844.

North On the East Boundary of sec. 35. T. 6 N. R. 3rd W.
 30.00 To a spring Corner N.
 40.00 Set a 7th supst from which,
 Gum 30 in dia. bet. S 72 E. 11 links dist. to

T. N. C. A. R. N. 277 278 Mr. Ind.

64.50	Reck 18 in dia: beam A 477. 24 lb ash;
80.00	Set apart for the ca of sw 24 25 from white, Elm 16 in dia: beam. A 25 & 4 lb ash; ra, Sugar. " " " S 477. 15 " " Sands and timber same as last mts.
2.00	On the East Boundary of sw 24. T. C. A. R. 277
16.50	Set apart for the ca of sw 24 25 from white, Elm 16 in dia: beam. A 41 & 22 lb ash; ra, Reck 15 " " " S 4377. 35 " "
62.00	Set apart for the ca of sw 13 24 from white, Elm 16 in dia: beam A 377. 35 lb ash; ra, Sugar 9 " " " S 37 & 50 " " Sands hilly timber Oak, etc.
5.00	On the East Boundary of sw 13. T. C. A. R. 277
40.00	Set apart for the ca of sw 13 24 from white, Reck 12 in dia: beam A 68 & 11 lb ash; ra, Sugar 16 " " " A 4877. 8 " "
44.00	Set apart for the ca of sw 12 23 from white, Sugar 16 in dia: beam A 777. 9 lb ash; ra, Reck 6 " " " A 15 & 23 " "
25.00	On the East Boundary of sw 12. T. C. A. R. 277

T. N. C. A. R. N. 277 278 Mr. Ind.

30.00	Set apart for the ca of sw 13 24 from white, Reck 9 in dia: beam S 277. 11 lb ash; ra, Sugar 12 " " " A 4077. 11 " "
80.00	Set apart for the ca of sw 13 24 from white, Reck 8 in dia: beam A 49 & 3 lb ash; ra, Elm 6 " " " S 577. 16 " " Sands hilly timber Oak,
4.00	On the East Boundary of sw 1. T. C. A. R. 277
10.00	Set apart for the ca of sw 13 24 from white, Elm 12 in dia: beam. A 4677. 7 lb ash; ra, Sugar 14 " " " S 9 & 17 " "
79.00	Set apart for the ca of sw 13 24 from white, Elm 12 in dia: beam. A 4677. 7 lb ash; ra, Sugar 14 " " " S 9 & 17 " "
81.00	Set apart for the ca of sw 13 24 from white, Elm 12 in dia: beam. A 4677. 7 lb ash; ra, Sugar 14 " " " S 9 & 17 " "
83.00	Set apart for the ca of sw 13 24 from white, Elm 12 in dia: beam. A 4677. 7 lb ash; ra, Sugar 14 " " " S 9 & 17 " "
	Sands hilly timber Oak.
	Surveyed by Alex. Holmes Sept 4 1877
	Subdivisions
40.00	Set apart for the ca of sw 13 24 from white, Sugar 20 in dia: beam. A 4277. 33 lb ash; ra, Reck 20 in dia: beam. A 6677. 25 lb ash; ra, Elm 10 " " " A 35 & 31 " "
80.00	Set apart for the ca of sw 13 24 from white, Reck 20 in dia: beam. A 6677. 25 lb ash; ra, Elm 10 " " " A 35 & 31 " "
	Sands hilly & hilly timbered with Oak & Hickory

T. N. C. A. R. N. 27th 2nd Mm. Ind.

East	On a Random line between Sec. 25 & 26. T. 6. N. R. 27 th
40.00	Set a trap for su. post.
80.00	Intersect the East Boundary 18 miles South of the post cor of sec. 25 & 26. Land the same.
West	On the True line between Sec. 25 & 26. T. 6. N. R. 27 th
40.00	Set the trap for su. post at the corner on the true line from white, Buck 20 in dia. beam A 23 E 91 st 1/2 and a w. 20. 10 " " " A 12 E 8 " "
80.00	Set the post cor of sec. 25, 26, 35 & 36
North	Between Sec. 25 & 26. T. 6. N. R. 27 th
40.00	Set a trap for su. post from white, Hick 10 in dia. beam A 64 N 81 st 1/2 E. 1/2 L. 10 " " " A 58 N. 23 " "
80.00	Set a post for the cor of sec. 23, 24, 25 & 26 from white, Buck 20 in dia. beam A 83 N. 59 1/2 E. 1/2 L. 10 " " " A 81 E 30 " "
	Land rolling Timber Oak, Hick & Buck
East	On a Random line between Sec. 24 & 25 T. 6. N. R. 27 th
40.00	Set a trap for su. post.
79.82	Intersect the East Boundary 45 miles South of the post cor of sec. 24 & 25. Land the same.
West	On the True line between Sec. 24 & 25 T. 6. N. R. 27 th
39.91	Set the trap for su. post at the corner on the true line from white, Dogwood 8 in dia. beam East 36th
79.82	Set the cor of sec. 23, 24, 25 & 26.
North	Between Sec. 23 & 24 T. 6. N. R. 27 th
8.50	Set a trap 20 in dia. in the line.
40.00	Set a trap for su. post from white,

T. N. C. A. R. N. 27th 2nd Mm. Ind.

	Buck 20 in dia. beam A 50 E 14 1/2 E. 1/2 L. 12 " " " A 57 N. 16 " "
80.00	Set a post for the cor of sec. 13, 14, 23 & 24 from white, L. 10 in dia. beam A 87 E 27 1/2 E. 1/2 Buck 18 " " " A 45 E 14 " "
	Land level and mt. Timber Buck & Elm
East	On a Random line between Sec. 23 & 24 T. 6. N. R. 27 th
40.00	Set a trap for su. post.
80.00	Intersect the East Boundary at the post cor of sec. 13 & 24. Land the same.
West	On the True line between Sec. 13 & 24. T. 6. N. R. 27 th
40.00	Set the trap for su. post at the corner on the true line from white, Buck 18 in dia. beam A 21 N. 81 st 1/2 E. 1/2 and a w. Dogwood 6 " " " A 73 E 23 " "
80.00	Set the post cor of sec. 13, 14, 23 & 24
North	Between Sec. 13 & 14 T. 6. N. R. 27 th
40.00	Set a trap for su. post from white, L. 10 in dia. beam A 65 E 16 1/2 E. 1/2 L. 12 " " " A 40 N 33 " "
80.00	Set a post for the cor of sec. 11, 12, 13 & 14 from white, Buck 8 in dia. beam A 67 N. 81 st 1/2 E. 1/2 L. 12 " " " A 40 E 34 " "
	Land rolling Timber Buck, Oak, & Hick
East	On a Random line between Sec. 12 & 13 T. 6. N. R. 27 th
40.00	Set a trap for su. post.
78.00	Intersect the East Boundary 8 miles South of the post cor of sec. 12 & 13. Land the same.

T. A. C. A. R. A. No 277 2nd Mr. Ind.

8000 N. N. N. 12 in dia. beam S. 16 E. 7 lbs. ash,
To the post cor of sw 21 22 23 24 25.

North Between Sec 21 22 T. 6. N. R. 277.
4000 Set a new post from which,
Beck 10 in dia. beam S. 17 N. 42 lbs. ash; ca,
Log post, 8, " " S. 21 N. 19, "
8000 Set a post for the cor of sw 15 16 21 22 from which,
Sugar. 8 in dia. beam. S. 18 E. 14 lbs. ash; ca,
N. Oak 12, " " S. 14 N. 14, "
Sands rich Lumber Oak, Ash, & Poplar.

East On a Random line between Sec 15 16 21 22 T. 6. N. R. 277.
4000 Set a timber post to sw post.
74.01 To a Branch 10 links and, 100 and 1.
80.04 Intersect the N. 15 line 10 links South of the post
cor of sw 14 15 21 22. Sands the same.

West On the Line line between Sec 15 16 21 22 T. 6. N. R. 277.
40.02 Set the timber post to sw post at the cor east on the line line
from which, Beck 10 in dia. beam S. 22 N. 12 lbs. ash
and ca Sugar. 8, " " S. 22 N. 16, "
80.04 To the cor of sw 15 16 21 22.

North Between Sec 15 16 T. 6. N. R. 277.
4000 Set a 1/2 cu post from which,
Poplar. 8 in dia. beam S. 16 E. 16 lbs. ash; ca,
Log 6, " " S. 11 N. 13, "
8000 Set a post for the cor of sw 9 10 15 16 from which,
a Black 20 in dia. beam S. 11 N. 11 lbs. ash; ca,
Sugar. 12, " " S. 1 E. 34, "
Sands rich Lumber Same as last mile.

T. A. C. A. R. A. No 277 2nd Mr. Ind.

East On a Random line between Sec 10 15 26 27 T. 6. N. R. 277.
4000 Set a timber post to sw post.
80.12 Intersect the N. 15 line at the post cor of sw 10 11 14 15
Sands the same as last mile.

West On the Line line between Sec 10 15 T. 6. N. R. 277.
40.06 Set the timber post to sw post at the cor east on the line line
from which, Beck 10 in dia. beam S. 18 E. 18 lbs. ash
and ca Sugar. 12, " " S. 8 E. 37, "
80.12 To the post cor of sw 9 10 15 16.

North Between Sec 9 10 T. 6. N. R. 277.
9.50 To a Beck 20 in dia. in the line.
40.00 Set a timber post to sw post from which,
Beck 6 in dia. beam S. 27 N. 13 lbs. ash; ca,
Log. 8, " " S. 1 E. 8, "
80.00 Set a post for the cor of sw 34 9 10 from which,
Sugar. 12 in dia. beam. S. 16 E. 15 lbs. ash; ca,
" " " S. 57 N. 3, "
Sands the same.

East On a Random line between Sec 3 4 10 T. 6. N. R. 277.
40.00 Set a timber post to sw post.
80.08 Intersect the N. 13 line at the cor of sw 2 3 11 11
Sands the same.

West On the Line line between Sec 3 4 10 T. 6. N. R. 277.
40.04 Set the timber post to sw post at the cor. east on the line line
from which, Beck 16 in dia. beam S. 17 N. 9 lbs. ash
and ca Sugar. 8, " " S. 11 E. 27, "
80.08 To the post cor of sw 3 4 9 10.

North Between Sec 3 4 T. 6. N. R. 277.

8000	Set apart for the cov of sec. 29. 30. 31. 32 from white, Oak 20 in dia. beam. N 86 W 23 links dist; 12, Maple 12 " " " N 77 E 38 " " Sunderbilly Timber Oak & Hick.
East	On a Random line between Sec. 29. 132 I. C. N. R. 272
4000	Set a trip for supst.
7300	To a Rock 50 links mid. Cornuc
8000	Intersect the N 86 line at the post cov of sec. 28. 29. 30. 31. 32 Sunderbilly same.
West	On the line between Sec. 29. 132 I. C. N. R. 272
4000	Set the trip for supst. at the cross in the line from white, Sugar 10 in dia. beam. N 85 E 68 links dist; 12, Hick 10 " " " N 77 W 103 " " 8000 To the post cov of sec. 29. 30. 31. 32
West	Return Sec. 30. 31 I. C. N. R. 272
2800	Set a Rock 12 in dia. in the line.
4000	Set a supst. from white, Sugar 12 in dia. beam. N 69 E 35 links dist; 12, Rock 20 " " " N 26 E 8 " " 7600 Intersect the West Road at 50 links South of the post cov of sec. 23. 36 I. C. N. R. 371 and set a post for " " " 30. 31 from white, Hick 10 in dia. beam. N 25 E 13 links dist; 12, Rock 12 " " " S 88 E 35 " " Sunderbilly Timber Oak & Hick. Apr. 14. 1814
North	Return Sec. 29. 130 I. C. N. R. 272
3750	To a Oak 20 in dia. in the line
4000	Set a supst. from white, Sugar 10 in dia. beam. N 3 E 37 links dist; 12,

8000	Return 8 in dia. beam. N 13 W 38 links dist; 12, Set apart for the cov of sec. 19. 20. 29. 30 from white, Rock 8 in dia. beam. N 44 W 18 links dist; 12, Sugar 12 " " " N 55 W 8 " " Sunderbilly same. as last mile
East	On a Random line between Sec. 20. 29 I. C. N. R. 272
4000	Set a trip for supst.
8012	Intersect the N 44 line at the post cov of sec. 20. 21. 28. 29. Sunderbilly same as last mile
West	On the line between Sec. 20. 29 I. C. N. R. 272
4000	Set the trip for supst. at the cross in the line from white, Rock 12 in dia. beam. N 27 W 27 links dist; 12, Oak 12 " " " N 68 E 20 " " 8012 To the post cov of sec. 19. 20. 29. 30.
West	Return Sec. 19. 130 I. C. N. R. 272
4000	Set a supst. from white, Rock 6 in dia. beam. N 75 W 6 links dist; 12, Oak 12 " " " N 42 E 12 " " 7600 Intersect the West Road at 20 links South of the post cov of sec. 24. 35 I. C. N. R. 371 and set apart for " " " 19. 30 from white, Rock 20 in dia. beam. N 6 E 24 links dist; 12, Sugar 8 " " " N 10 E 16 " " Sunderbilly Timber Oak & Hick
North	Return Sec. 19. 130 I. C. N. R. 272
4000	Set a supst. from white, Rock 12 in dia. beam. East 1 link dist;
8000	Set apart for the cov of sec. 17. 18. 19. 20 from white, Hick 20 in dia. beam. N 3 E 19 links dist; 12,

I. N. C. A. R. A. D. W. D. M. M. Ind.

Dogwood 4 in diam. bears N 39 E 8 links dist.
 Same the same.

East	On a Random line between Sec 17 & 20 T. 6. N. R. 2 W.
40.00	Set a temp. post
80.00	Intersect the A. S. line at the post cor. of sec. 16 & 17 20 & 21. Same the same as last mile.
West	On the True line between Sec 17 & 20 T. 6. N. R. 2 W.
40.00	Set the temp. post at the ar. dist. on the true line from which, Buck 10 in diam. bears S 80 E. 11 links dist. Maple Sugar 10 " " S 10 W 9 " "
80.00	to the post cor. of sec. 17, 18, 19 & 20
West	Return Sec 18 & 19 T. 6. N. R. 2 W.
29.50	to a Buck 20 in diam. in the line
110.00	Set a post from which Buck 10 in diam. bears S 78 E. 48 links dist. to Maple 20 " " N 61 W 28 " "
50.00	to a Buck 150 links mid. corner S. C.
74.80	Intersect the West Boundary 350 links South of the post cor. of sec. 13 & 24 T. 6. N. R. 3 W. and set a post for the cor. of sec. 18 & 19 from which Buck 10 in diam. bears South 14 links dist. to Hick 12 " " S 43 W 12 " " Same the same.
North	Between Sec 17 & 18 T. 6. N. R. 2 W.
40.00	Set a post from which Buck 20 in diam. bears S 43 W 14 links dist. to Lynn - 12 " " N 27 W 10 " "
76.00	to a Buck 25 links mid. corner S. W.
80.00	Set a post for the cor. of sec. 7, 8, 17 & 18 from which Buck 12 in diam. bears S 48 E. 2 links dist. to

I. N. C. A. R. A. D. W. D. M. M. Ind.

Sugar 4 in diam. bears N 81 W 15 links dist.
 Same the same.

East	On a Random line between Sec 3 & 17 T. 6. N. R. 2 W.
4.50	to a Buck 25 links mid. corner S. W.
40.00	Set the Temp. post for the cor. of 14 Sec.
80.00	Intersect the A. S. line 10 links South of the post cor. of Sec. 8, 9, 16 & 17. Same as last mile.
West	On the True line between Sec 8 & 17 T. 6. N. R. 2 W.
40.00	Set the temp. post for the cor. of 14 Sec. at the ar. dist. on the true line from which a Dogwood 8 in diam. bears N 31 W 15 links dist. to So. 16 " " S 58 E 6 " "
80.00	sec. cor.
West	Between Sec 7 & 18 T. 8 E. A. R. 3 W.
1.50	to a Buck 12 in diam. in the line
40.00	Set a post for the cor. of 14 Sec. from which a Buck 8 in diam. bears S 75 W 14 links dist. to So. 16 " " S 75 E 13 " "
72.76	Intersect the West Boundary 375 links South of the post cor. of Sec. 12 & 13 T. 6. N. R. 3 W. Set a post for the cor. of Sec. 7 & 18 from which a Buck 10 in diam. bears N 43 W 18 links dist. to Maple 8 " " S 43 E 10 " " Same Hilly Timber Oak & Hick.
North	Return Sec 7 & 18 T. 6. N. R. 2 W.
40.00	Set a post from which Immord 6 in diam. bears S 1 E 91 W dist. to Buck 12 " " S 44 W 77 " "
80.00	Set a post for the cor. of sec. 5, 6, 7 & 18 from which Buck 7 in diam. bears S 80 E 22 links dist. to

T. N. C. N. R. N. 2nd Mm. Ind.

Log road 6 in dia: trees 587 1/4 the ash
Sands the same.

East Oak and am line between Sec 578 T. 6 N. R. 27 W.
37.00 To a Rock from a Spring 5 links wide. Secured.
40.00 Set a trap for 1/4 sec post.
80.05 Intersect the N. 5. line at the post cor of sec 458
79 Sands the same.

West Oak and am line between Sec 578 T. 6 N. R. 27 W.
40.14 Set the trap for 1/4 sec post at the arched on the line line
from which Rock 10 in dia: trees 51 E. 13 the ash
and a Sugar 12 " " " 137 1/2 " "
80.08 To the post cor of sec 5. 6. 7 1/2.

West Return Sec 6. 17 T. 6 N. R. 27 W.
40.00 Set a 1/4 sec post from which
Sugar 8 in dia: trees 58 E. 20 the ash; 12
Rock 20 " " " West 35 " "
69.76 Intersect the West Bound 1468 links South of the
post cor of sec 1412 T. 6 N. R. 27 W. and set a
post " " 617 from which
Log road 6 in dia: trees 54 E. 17 links ash; on
Rock 6 " " " South 2 " "
Sands the same as last mile.

North Return Sec 576 T. 6 N. R. 27 W.
34.50 To a Rock 20 in dia: in the line
40.00 Set a 1/4 sec post from which
N. 5. 6 in dia: trees 54 E. 10 the ash; 12
Rock 10 " " " 176 1/2 " "
87.98 Intersect the N. Bound 1398 links East of the post cor
of sec 3435 T. 7 N. R. 27 W. and set a post for the ca

T. N. C. N. R. N. 2nd Mm. Ind.

of sec 576 from which

Sec. 20 in dia: trees 185 E. 13 links ash; 12
Log road 6 " " " 166 E. 10 " "
Sands the same and very brushy. Timber Oak, Poplar
& Hick. April 13 1874

Surveyed by
Arthur Hennie.
Asst. Sur.

I certify that the foregoing Transcript of the field
notes of Township N. 6. North of Range N. 27 West
of the 2nd Principal Meridian, in Indiana has
been compared with the Original notes in this Office
and found to be correct.
Surveyor General's Office,
Cincinnati Mo. 16. 1874

Sur. General.